

Technical specs

Type of fuel	Wood
Recommended surface	500 to 2,100 sq. ft.
Blower	2 x 100 CFM
Color	Metallic black
Exterior dimensions	36 3/4"W x 26 1/2"D x 43 1/4"H
Type of chimney	2,100° F / 650° C
Recommended chimney diameter	6" or (for 7" see the owner's manual)
Centre line of flue outlet to the back	10 1/8"
Centre line of flue outlet to the side	18"

Manufacturer: Selkirk

Brand: Ultra-Temp (UT)

Type: 1" Solid Pack

Manufacturer: Selkirk

Brand: Super Pro (SPR)

Approved chimney manufacturers, brands, and types

Type: 1" Solid Pack

Manufacturer: Selkirk

Brand: Super Vent (JSC)

Type: 1" Solid Pack

Manufacturer: Selkirk

Brand: Hart & Cooley (TLC)

Type: 1" Solid Pack

Manufacturer: Selkirk

Brand: Sure-Temp (ST)

Type: 1" Solid Pack

Manufacturer: Selkirk

Brand: CF Sentinel (CF)

Type: 2" Solid Pack

Manufacturer: Selkirk

Brand: Super Pro 2100 (ALT)

Type: 2" Solid Pack

Manufacturer: Selkirk

Brand: Super Vent 2100 (JM)

Type: 2" Solid Pack

Manufacturer: Selkirk

Brand: UltimateOne

Type: 1" Solid Pack

Manufacturer: Security Chimney

Brand: ASHT+

Type: 1" Solid Pack

Manufacturer: Security Chimney

Brand: S-2100 +

Type: 2" Solid Pack

Manufacturer: Simpson Dura Vent

Brand: Dura Tech

Type: 1" Solid Pack

Manufacturer: Simpson Dura Vent

Brand: Dura Plus HTC

Type: 2" Solid Pack

Manufacturer: Simpson Dura Vent

Brand: Dura Plus

Type: AC Triple Wall

Manufacturer: ICC

Brand: Excel 2100

Type: 1" Solid Pack

Manufacturer: Metal Fab

Brand: Temp Guard

Type: 1" Solid Pack

Manufacturer: American Metal

Brand: HSS

Type: AC Triple Wall

Manufacturer: American Metal

Brand: HS

Type: AC Triple Wall

Manufacturer: Olympia Chimney

Brand: Ventis

Type: 1" Solid Pack

Manufacturer: FMI (U.S.A. only)

Brand: AC **Type:** AC Triple Wall

Minimum chimney height	15'
Firebox dimensions	20 5/8"W x 17 3/4"D
Log positioning	East / West or North / South
Maximum log length	21"
Door opening dimensions	25 3/4"W x 10 5/8"H
Type of door	Double door, glass with cast iron frame
Minimum clearances to combustibles * (Data expressed in inches. 1 inch = 25.4 mm)	
Sidewall	17"
Side facing	0"
Mantle (from floor)	50"
Back wall	0"
Floor	0"
Sides	0"
Non-combustible surface (side)	0"
Non-combustible surface (top)	0"
* The information given on the certification label affixed to the appliance always overrides the information published in any other media (owner's manual, catalogues, flyers, magazines and/or web sites).	
Glass surface	277 sq. in.
Weight	350 lb (159 kg)
Warranty	Limited lifetime
Test standard - safety	ULC-S610, UL 127, NFPA 211 and CSA B365, as applicable in Canada and USA

Test standard - emissions

EPA / CSA B415.1